



## ADDITIONAL INFORMATION

|                             |                |
|-----------------------------|----------------|
| <b>Weight</b>               | 0.06 kg        |
| <b>Dimensions</b>           | 9.5 × 7 × 4 cm |
| <b>Carton Qty</b>           | 136            |
| <b>Pricing Unit</b>         | Each           |
| <b>Min Order Qty</b>        | 1              |
| <b>ARTG ID</b>              | 375867         |
| <b>GMDN Code</b>            | 45607          |
| <b>Medical Device Class</b> | Class 2a       |
| <b>UNSPSC</b>               | 42181800       |
| <b>Tax Schedule</b>         | Taxable        |
| <b>Is Serialized Item</b>   | No             |
| <b>Is Dangerous Good</b>    | No             |

## PRODUCT DESCRIPTION

A small pulse oximeter for measuring the pulse oxygen saturation, pulse rate and perfusion index through the finger.

Suitable for monitoring adult & paediatric patients in clinics, hospitals and at home.

### Features:

Splash and drop resistant design

OLED display of SpO2, PR, PI, pulse bar & waveform

Spot check and continuous pulse oximeter measurement modes

Pulse rate analysis for spot check measurement

Up to 12 groups SpO2 data storage

Audio & visual alarm with low battery indication

Automatic power on/off

Multi direction display

Artefact removal & anti-motion

Accurate & sensitive

## **Pulse Oximeter Specification:**

### **SpO<sub>2</sub>**

Transducer: Dual-wavelength LED sensor

Measuring range: 35-100%

Measuring accuracy:  $\leq 2\%$  range from 70-100%

### **Pulse Rate**

Measuring range: 30-240bpm

Measuring accuracy:  $\pm 2$ bpm or  $\pm 2\%$  (whichever is the greater)

### **Perfusion Index**

Display range: 0-20%

### **Default Alarm Limit**

SpO<sub>2</sub> low limit: 90%

Pulse rate high limit: 120bpm

Pulse rate low limit: 50bpm

### **Measuring Mode**

30 seconds spot check mode

Continuous mode

### **Dimensions, Weight & Power**

Dimensions: 56x34x30mm (L x W x H)

Weight: 52g

Power: 2 x AAA alkaline battery